

## Floor varnish

one component parquet varnish

### PRODUCT DESCRIPTION

Top quality modified urethane alkyd base, one component glossy varnish for parquets. Suitable for the coating of internal wooden floors. It has got great toughness, gloss, adhesion and resistance to abrasion and scratching. It maintains its high gloss and woods decorative effect for many years.



### TECHNICAL CHARACTERISTICS

<b>Specific gravity</b>	0,93	gr/cm <sup>3</sup> (23°C)	ISO EN2811.01 - 2011
<b>Viscosity</b>	500 - 700	mPas (23°C)	ISO EN 2555 - 1999
<b>Solids content by weight</b>	47 - 49	%	ISO EN 3251 - 2008
<b>Solids content by volume</b>	50 - 52	%	ISO EN 3233 - 1998

### GENERAL CHARACTERISTICS

<b>Coverage</b>	10 - 15m <sup>2</sup> /Lt on properly prepared surfaces
<b>Dilution</b>	3-5% White Spirit
<b>Drying</b>	2-4 hours depending on conditions
<b>Shades</b>	Clear
<b>Recommended Primer</b>	Wood Care

### APPLICATION INSTRUCTIONS

In a primed and well-prepared surface apply 2-3 coats Floor varnish. Wait about 6 hours between the coats. In old varnished floor we sand and clean well before the floor varnish application. Minimum temperature for application is 10°C.

### APPLICATION CONDITIONS

Do not apply at temperatures below 6°C and above 40°C and at relative humidity above 80%. Adverse conditions in the application can alter the final properties of product.

## APPLICATIONS TOOLS

### Brush, roller, airless gun

During working keep tools "liquid" in the container. Drain well the product of the tools back in the box and clean immediately with White spirit. If product dries only with strong detergents. Do not empty washings into the groundwater.



## STORAGE

After use close well the container to keep in good condition for future use. Store in a cool place. Protect from freezing and direct sunlight.

## PACKAGING

It is delivered in metallic containers of **750ml, 3Lt**

## VOC CLASSIFICATION (VOLATILE ORGANIC COMPOUND)

Product Category A/f (SB) 'Interior/exterior minimal built woodstains' of the EU legislation 2004/42/EU. Maximum limit VOC value of category: 700gr/lit. Maximum VOC concentration of ready to use product 695gr/lit. Product in compliance after 2010 (Phase II).

## WASTE MANAGEMENT

For leftovers of product required special management, so as not to pollute the environment. Therefore should not be disposed of with household waste. For more information about the disposal and collection of waste, please contact your local government agencies.

## HYGIENE & SAFETY INSTRUCTIONS

### HAZARDS STATEMENTS:

**H226:** Flammable liquid and vapour • **H372:** Causes damage to organs through prolonged or repeated exposure • **H412:** Harmful to aquatic life with long lasting effects.

### PRECAUTIONARY STATEMENTS:

**P201:** Obtain special instructions before use • **P260:** Do not breathe fume and spray • **P280:** Wear protective gloves/protective clothing/eye protection/face protection • **P303+P361+P353:** IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower • **P501:** Dispose of contents/container according to local and national regulations. Use without dilution. **CONTAINS:** Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), Cobalt bis(2-ethylhexanoate) and 2-boutanone oxime. May cause allergic reactions



**DANGER**

For more information, consult the MSDS.



The company is certified to standards  
EN ISO 9001:2008 / EN ISO 14001:2004

Version: July 2016  
This issue replaces all previous